

Data sheet

IM 053CAN - CANopen server (053-1CA00)

Technical data

Order no.	053-1CA00
------------------	------------------

Type	IM 053CAN - CANopen server
Module ID	-

General information

Note	-
------	---

Features	16x Rx and 16x Tx PDOs 2x SDOs PDO-Linking PDO-Mapping: fix Up to 64 peripheral modules
----------	---

Technical data power supply

Power supply (rated value)	DC 24 V
----------------------------	---------

Power supply (permitted range)	DC 20.4...28.8 V
--------------------------------	------------------

Reverse polarity protection	yes
-----------------------------	-----

Current consumption (no-load operation)	90 mA
---	-------

Current consumption (rated value)	0.95 A
-----------------------------------	--------

Inrush current	3.9 A
----------------	-------

I ² t	0.14 A ² s
------------------	-----------------------

Max. current drain at backplane bus	3 A
-------------------------------------	-----

Max. current drain load supply	10 A
--------------------------------	------

Power loss	3 W
------------	-----

Status information, alarms, diagnostics

Status display	yes
----------------	-----

Interrupts	yes, parameterizable
------------	----------------------

Process alarm	no
---------------	----

Diagnostic interrupt	yes, parameterizable
----------------------	----------------------

Diagnostic functions	yes, parameterizable
----------------------	----------------------

Diagnostics information read-out	possible
----------------------------------	----------

Supply voltage display	green LED
------------------------	-----------

Service Indicator	-
-------------------	---

Group error display	red LED
---------------------	---------

Channel error display	none
-----------------------	------

Hardware configuration

Racks, max.	1
-------------	---

Modules per rack, max.	64
------------------------	----

Number of digital modules, max.	64
---------------------------------	----

Number of analog modules, max.	64
--------------------------------	----

Communication

Fieldbus	CANopen
----------	---------

Type of interface	CAN
-------------------	-----

Connector	Sub-D, 9-pin, male
-----------	--------------------

Topology	Linear bus with bus termination at both ends
----------	--

Electrically isolated	yes
-----------------------	-----

Number of participants, max.	127
------------------------------	-----

Node addresses	1 - 127
Transmission speed, min.	10 kbit/s
Transmission speed, max.	1 Mbit/s
Address range inputs, max.	128 Byte
Address range outputs, max.	128 Byte
Number of TxPDOs, max.	16
Number of RxPDOs, max.	16
Supported profile	-
Supported transfer cycle	-
Cyclic data size per node	-
Max. Number of nodes	-
Supported communication method	-
Supported command "Cyclic"	-
Supported command "Event driven"	-
Supported command "Message"	-

Datasizes

Input bytes	-
Output bytes	-
Parameter bytes	-
Diagnostic bytes	-

Housing

Material	PPE / PPE GF10
Mounting	Profile rail 35 mm

Mechanical data

Dimensions (WxHxD)	48.5 mm x 109 mm x 76.5 mm
Net weight	162.5 g
Weight including accessories	162.5 g
Gross weight	180 g

Environmental conditions

Operating temperature	0 °C to 60 °C
Storage temperature	-25 °C to 70 °C

Certifications

UL certification	yes
KC certification	yes
UKCA certification	yes
ChinaRoHS certification	yes